BT-1162 2D WIRED HAND-HELD BARCODE SCANNER



SPECIFICATIONS

PERFORMANCE

Technology: CMOS.

Light Source: green light (Scan), White light (bright).

MTBF: 100.000 hours.

Scan mode: manual, continuous or automatic activation on support.

Image resolution: 640 x 480 pixels. Scan speed: 60 fps/s.

Depth of field: Code 39 (5mil): 7 a 16 cm, Code 39 (13mil): 7 a 32 cm, QR code

(15mil): 3 a 18 cm, Code 128 (20mil): 6 a 35 cm.

Min. resolution: ≥3mil.

Scan angle: rotation 360°, tilt ±65°, deflection ±65°.

Print contrast: PCS: 20%.

Scanner: allows scanning directly on the monitor or smartphone screen.

Operating voltage: 5 VDC +/- 0.25 VDC.
Operating current: less than 300mAh.
Standby current: less than 35mAh.
Usability: Plug & Play.

2.4GHz Communication distance: Up to 150 meters in open space. Bluetooth Communication distance: Up to 10 meters in open space.

INTERFACE

Interfaces: USB-HID, USB-COM, 2.4GHz and Bluetooth.

BATERIA

Type: 2200mAh rechargeable lithium battery (guarantees 16h of

continuous work).

Charger: charging base or USB C cable (optional).

Charging time: approximately three hours.

Stand-by: up to 6 months.

DECODING

1D: Codabar, Code 11, Code 39, Code 32, Interleaved 2 of 5,

Industrial 2 of 5, Matrix 2 of 5, Code 93, Code 128, GS1-128, UPC-A, UPC-E, EAN 8, EAN 13, GS1 DataBar (RSS14), GS1 DataBar Limited, GS1 DataBar Expanded and more. Allows scanning

barcodes with more than 60 characters.

2D: PDF417, Micro PDF417, QR Code, Micro QR, Data Matrix, Aztec

Code.

Internet Banking: Febraban and Danfe compatible.

PHYSICAL CHARACTERISTICS

Dimensions: $L \times W \times H$: 174mm \times 65,7mm \times 83,5mm.

Material: ABS+PC

Weight: 185g (scanner) 220g (scanner with charging base). Indicators: Adjustable beep (volume) and LED light (green).

Cable length: 1 m.

ENVIRONMENTAL CHARACTERISTICS

Temperatura de operação: -20°C to 50°C.
Temperatura de armazenagem: -40°C to 70°C.

Humidity: 5% to 95% relative humidity, non-condensing.

Light levels: 0-100,000 Lux. ESD protection: 16KV. Drop resistance: 3 m.

Sealing: IP54 and sealed to resist airborne particles.

DOCUMENTS

Documents: Programming manual and quick reference guide.

COMPATIBILITY

Compatible with: Windows 98, 2000, XP, ME, Vista, Windows 7, 8, 10, 11 (32&64bits) macOS, Linux, Android and IOS.

REGULATIONS

Safety and approvals: BT-1162 has the necessary safety certifications and regulatory

approvals for protected use.

Compliance: CE, FCC, DOC. Environmental compliance: RoHS.

ACCESSORIES

Included: Removable USB cable and 2.4GHz wired charging base.

WARRANTY

Warranty: 1 year

