-3300 Plus



SPECIFICATIONS

PERFORMANCE

Technology: Area Imager.

Light source: Blue LED (illumination), red LED (scanning) 650mn +/-10nm.

MTBF: 100,000 hours.

Scan mode: Continuous and automatic. Image resolution: 1280 x 1080 pixels.

Scan speed: 60 fps/s.

Depth of field: Code 39 (5mil): 1-15cm, UPC (13mil):

1-33cm, Code 39 (20mil): 1-40cm, QR Code (20mil): 1-28cm.

Min resolution:

Scan angle: Rotation 360°, tilt ±60°, defletion ±70°.

Scan direction: Omnidirectional. Print contrast: PCS: 20%.

Scanner: Allows reading directly on the monitor and smartphone screen. It

also scans paper and film codes.

5 VDC +/- 0.25 VDC. Operating voltage: Operating current: Less than 200mAh. Standby current: Less than 150mAh.

Motion Tolerance: 3.8m/s.

INTERFACE

Interfaces: Removable USB;

USB-VCP; RS232 Serial Port.

DECODING

UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), 1D:

> ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5 (Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128, ISBT 128, Code 93, Code 11 (USD-8), MSI/Plessey, UK/Plessey, China Post, China Finance, Telepen, GS1 DataBar (formerly RSS) variants, PDF417,

FEBRABAN, DANFE.

2D: PDF417, MicroPDF417, QR-code, MicroQR, Data Matrix, QR, Aztec.

PHYSICAL CHARACTERISTICS

Dimentions: L×W×H: 83mm×150mm×150mm.

High impact ABS+PC with flame retardant material. Material:

Color: Black.

Weight: 576g without cable.

Adjustable beep tone/volume and LED light (blue and red). Indicators: Buttons: BT-3300 Plus has a button to switch between different tones and a button to switch between reading 1D, 1D and

2D or 2D codes only.

Cable length: 1.8 m.

ENVIRONMENTAL CHARACTERISTICS

Operating Temperature: -20°C to 55°C. Storage temperature: -20°C to 60°C.

5% to 95% relative humidity, non-condensing. Humidity:

Light Levels: 0-70,000 Lux. ESD protection: 16KV. Drop resistance:

IP54 and sealed to resist suspended particles. Sealing:

DOCUMENTS Documents:

Programming manual and quick reference guide.

COMPATIBILITY

Windows 98, 2000, XP, ME, Vista, Windows 7, 8, 10, 11 (32 & 64 bits), Compatible with:

MacOS, Linux, Android and IOS.

REGULATIONS

BT-3300 Plus has the safety certifications and regulatory Security and approvals:

approvals required for protected use.

Compliances: CE & FCC DOC. Environmental compliance:

ACCESSORIES

Included: Removable USB cable.

WARRANTY

Warranty: 1 year.

